

## Fluid for Seldén Hydraulic Systems

Seldén changed from vegetable base to mineral base fluid in 2005.

For system service / top up, it is preferable to use the identical fluid.

It is acceptable to add fluid from other manufacturers, providing that they have the same base (vegetable or mineral), and are of a similar specification.

If you wish to change from vegetable to mineral base fluid, the system must be completely drained.

### Oil Replacement intervals:

In normal use we recommend the oil is changed along with the filter at least every four years.

Systems manufacture date	Before May 2005	After May 2005
Hydraulic fluid used	Binol Hyd 46	Hydro HYNDLA HYDRAULIC OIL 46
Fluid base	Vegetable Oil	Mineral Oil
Specification		ISO VG 461 DIN 51.524
ISO Viscosity Class	VG 46	VG 46
Environment	Biodegradable	
Equivalent Products	BP Biohyd 46	Statoil HYDRAWAY HVXA 46 Shell TELLUS 46 Castrol HYSPIN AWS 46



[www.seldenmast.com](http://www.seldenmast.com)

**Sweden:** Seldén Mast AB • Tel: +46 (0)31 69 69 00 • [info@seldenmast.com](mailto:info@seldenmast.com)

**UK:** Seldén Mast Ltd. • Tel: +44 (0)1329 50 40 00 • [info@seldenmast.co.uk](mailto:info@seldenmast.co.uk)

**USA:** Seldén Mast Inc. • Tel: +1 843-760-6278 • [info@seldenus.com](mailto:info@seldenus.com)

**Denmark:** Seldén Mast A/S • Tel: +45 39 18 44 00 • [info@seldenmast.dk](mailto:info@seldenmast.dk)

**the Netherlands:** Seldén Mid Europe B.V. • Tel: +31 (0)111-698 120 • [info@seldenmast.nl](mailto:info@seldenmast.nl)

**France:** Seldén Mast SAS • Tel: 33 (0) 251 362 110 • [info@seldenmast.fr](mailto:info@seldenmast.fr)

SELDÉN and FURLEX are registered trademarks of Seldén Mast AB