

Boom brackets

Fixed boom brackets

The Seldén boom brackets and toggles are manufactured from cast aluminium and come with tack attachment and, if required, reef hooks.

Boom section	Mast section		Boom bracket, Art. no. Aluminium mast/Carbon mast		Dimension mm	Fasteners, Aluminium masts Art. no.	Fasteners, Carbon masts Art. no.
	Alu.	Carbon	Toggle and tack attachment	Toggle, tack attachment and reef hooks			
B087	C080-C096	CC077-CC095	508-732-03/53	508-732-05/55	Bracket Height: 70 Width: 62 Toggle (528-094) Width: 15 Hole: Ø 8	8 pop rivets 167-018 (Ø 4.8 x 12.7)	8 pop rivets 167-033 (Ø 4.8 x 6-8.5)
	C106-C126	CC105-CC125	508-731-03/53	508-731-05/55	Bracket Height: 97 Width: 47 Toggle (528-094) Width: 15 Hole: Ø 8		8 pop rivets 167-053 (Ø 4.8 x 8.5-11)
	C126-C139	CC125-CC138	508-788-03/53	508-788-05/55	Bracket Height: 130 Width: 55 Toggle (528-109) Width: 15 Hole: Ø 8	10 pop rivets 167-006 (Ø 4.8 x 16.5)	10 pop rivets 167-053 (Ø 4.8 x 8.5-11)
B104	C080-C096	CC077-CC095	508-732-03/53	508-732-05/55	Bracket Height: 70 Width: 62 Toggle (528-094) Width: 15 Hole: Ø 8	8 pop rivets 167-018 (Ø 4.8 x 12.7)	8 pop rivets 167-033 (Ø 4.8 x 6-8.5)
	C106-C139	CC105-CC138	508-731-03/53	508-731-05/55	Bracket Height: 97 Width: 47 Toggle (528-094) Width: 15 Hole: Ø 8		8 pop rivets 167-053 (Ø 4.8 x 8.5-11)
	C126-C139*	CC125-CC138*	508-788-03/53	508-788-05/55	Bracket Height: 130 Width: 55 Toggle (528-109) Width: 15 Hole: Ø 8	10 pop rivets 167-006 (Ø 4.8 x 16.5)	10 pop rivets 167-053 (Ø 4.8 x 8.5-11)
B120	C106-C116	CC105-CC125	508-731-04/54	508-731-06/56	Bracket Height: 97 Width: 47 Toggle (528-036) Width: 20 Hole: Ø 10	8 pop rivets 167-018 (Ø 4.8 x 12.7)	8 pop rivets 167-053 (Ø 4.8 x 8.5-11)
	C126-C139*	CC125-CC138*	508-788-04/54	508-788-06/56	Bracket Height: 130 Width: 55 Toggle (528-108) Width: 20 Hole: Ø 10		10 pop rivets 167-006 (Ø 4.8 x 16.5)

*Max RM 10 kNm.

Separate reef hooks/tack attachment

Boom bracket, Art. no.	Reef hook, Art. no.	Tack attachment, Art. no.
508-731- 508-732-	536-115	536-117
508-788-	536-118-01	536-119-01



Boom bracket with tack attachment and reef hooks for slab reef booms.



Boom bracket with tack attachment for Single Line booms.

Sliding boom bracket

This bracket slides in the sail groove. A stop rivet is fitted to the mast in order to prevent the upper edge of the boom from being below the measurement band. A downhaul can be attached to the lower end of the bracket.



This type of boom bracket is specified in some class rules.

Boom section	Mast section	Boom bracket, Art. no.		Dimension, mm
		Toggle and tack attachment, Art. no	Toggle, tack attachment and reef hooks, Art. no.	
B087- B104	C080- C139	511-518-01	511-518-02	Bracket (AL) Height: 60 Toggle Width: 15 (ST) Hole: Ø 8



Photo: Fiona Brown. Quarter tonner.