

# Keel-stepped and deck-stepped masts,

C-sections and F-sections

The T-base and deck ring systems are made to fit both Seldén's conventional mast sections and their matching furling sections. They are also made to create deck order among halyards. The blocks are fastened to the T-base or deck ring with a removable stainless steel shaft, which makes it easy to rearrange the blocks. The deck ring incorporates a state-of-the-art mast wedging system.



Eyes for halyard stowage



*T-base for deck-stepped masts with integrated block fastenings.  
Just remove stainless steel shaft to fit up to eight blocks.  
A two-piece shaft is available for narrow deck layouts.*

# Keel-stepped masts,

## C-sections and F-sections

The deck ring system for keel-stepped masts has a multi-purpose design. The forward composite wedge with rubber chocking is removed while bringing the mast through the deck ring. When refitted and tightened it slides down/aft and secures the mast.

The tie rod has four fixed settings, each with plenty of leeway for adjustment.

The T-base for keel-stepped masts can be adjusted longitudinally (fore-and-aft) with the mast still in place. Just ease off the rigging and turn the adjusting screw of the T-base until the required prebend and rake are achieved.

The underside of the heel plug is convex, in order to allow rake without subjecting the mast section to point loading.



Remove the wedge.



Step the mast and replace the wedge.



Secure the mast by tightening the nut on the wedge.



Block stand-up, rubber.



Adjustable T-base. Adjusts easily with mast still in place.



Convex underside of heel plug – distributes compression load evenly on the mast section.

## Deck ring system

Mast section	Deck ring, incl. 4 halyard attachments + axle for integrated blocks*, (dim., mm)	Separate block-axle	Separate 2-piece block axle	Locking screw for block axle	Block stand-up rubber	Wedge	Shaped rubber wedges	
							Fore 1 off	Aft 2 of
C156	533-030-01 (275 x 240)	166-274	-	155-624	319-512	530-208	530-209	530-221
C175, F176	533-029-01 (316 x 242)	166-270	-	-			319-669	530-210
C193, F194					530-209	530-212		
C211, F212	533-022-01 (349 x 300)	166-221	166-260-01	-	319-680	530-211	530-210	530-213
C227, F228							530-209	530-212
C245, F246	533-023-01 (401 x 344)	166-224	166-261-01	155-609	-	530-214	530-210	530-213
C264, F265							530-209	530-212
C285, F286	533-024-01 (450 x 372)	-	-	-	-	530-216	530-210	530-213
C304, F305							530-209	530-212
C321, F324	533-039-01 (520 x 382)	166-295	n/a	153-014	-	530-216	530-241	530-242
C365, F370	533-038-01 (573 x 410)	166-229	n/a	-	-	530-218	C365 530-245 F370 530-241	
F406	533-036-01 (603 x 403)	n/a	n/a	n/a	n/a	n/a	530-575	530-575

\* Blocks are not included.



Deck ring with moulded mast coat.

Tie rods with four fixed settings – plenty of leeway for adjustment.



### Mast coats (moulded), C-sections and F-sections

C-sections and F-sections

Mast section	Mast coats Art. No.	Hose clips, Art. No.	
		Upper	Lower
C156	530-053	312-201	312-204
C175, F176	530-054	312-202	312-205
C193, F194	530-055	312-203	312-206
C211, F212	530-056	312-204	312-206
C227, F228			
C245, F246	530-058	312-205	2 x 312-203
C264, F265	530-060	312-207	2 x 312-205
C285, F286			
C304, F305	530-038 + 530-040 (canvas)	-	2 x 312-205
F324			

### Replacement coats,

Can be fitted with the mast stepped.

Section	Repl. coat	Section	Repl. coat
C156	530-053-51	C245, F246	530-058-51
C175, F176	530-054-51	C264, F265	530-058-51
C193, F194	530-055-51	C285, F286	530-060-51
C211, F212	530-056-51	C304, F305	503-060-41
C227, F228	530-056-51	-	-

Tie-rod fittings	Tie-rod		T-base			
	Cover	Adjustable	T mm	Fixed	T mm	
508-259-01	508-260	510-152-01	12	-	-	
		510-134-01		510-136	33	
		510-143-01	20	510-141	44	
508-259-03	-	510-125-02	45	-	-	
		-		-	-	
Tie rod fitted to keelson	-	510-190-01	70	-	-	

